

CP-4221-30x

# FLIR QUASAR™

1080p sWDR PTZ Camera



## HIGHEST QUALITY. LOWEST BANDWIDTH. PREDICTABLE STORAGE.

The Quasar family includes an HD 1080p PTZ camera that delivers broadcast video quality and guaranteed frame rates in high motion, complex and low light scenes.

The FLIR Quasar CP-4221-30x HD PTZ delivers one of the lowest bandwidths in the industry through its advanced H.264 motion processing technology.

Now you can reduce your Total Cost of Ownership (TCO) by deploying this high quality surveillance camera that easily handles the wide variations in motion and lighting found in airports, city surveillance projects, critical infrastructure sites, commercial offices and campuses.

## HD Broadcast Quality H.264 Video

- Multi-streaming at the highest frame rates
- HD 1080p at the lowest bit rate
- Included analytics:
  - Tamper Detection
  - Multi-zone VMD
- Wide Dynamic Range (WDR)
- 30x Indoor or Outdoor continuous auto focus HD precision zoom lens
- Privacy Masking
- Bi-directional audio
- PTZ models offer 24 VAC and PoE options
- Web interface for viewing, control

### Features

- Broadcast quality multi-stream H.264 video
- Guaranteed frame rates in complex, high motion scenes
- Broadcast quality motion processing
- Auto-tune technology
- Edge-based recording and meta data

### Benefits

- Crisp, clean video for supreme identification
- Maintains evidentiary integrity of video in challenging surveillance conditions
- Maintains lowest bit rates regardless of motion/scene complexity; lowers TCO with predictable storage and network requirements
- Best out-of-the-box experience with no adjustments; auto scene adaptation eliminates service calls
- Protects against network outages using Storage on the Edge

## General Specifications

Camera	
Image Sensor	1/2.8" CMOS
Maximum Resolution	1920x1080 (HD 1080p)
Scanning Mode	Progressive
Optical Zoom	30x
Digital Zoom	1 to 12 variable
Focal Lengths	4.3 to 129 mm
Focus Mode	Auto / Manual
White Balance	Auto / Indoor / Outdoor / ATW / Manual
Iris Control	Auto / Manual
Digital Slow Shutter (DSS)	1.0 to 1 / 10,000 with up to 32x sensitivity boost in color or night mode
AGC Control	Auto / Manual
Back Light Compensation	On / Off
Wide Dynamic Range (Multi-shutter)	On / Off
3D Noise Reduction	On / Off
Tamper Detection	On / Off
Electronic Image Stabilization	On / Off
Video Motion Detection	On / Off - up to 10 independent zones
Privacy Zones	On / Off - 16 zones
Day / Night: IR Cut Filter	Auto / Manual
Image Rotation	Normal / Flip / Mirror
Minimum Illumination	0.3 (color) / 0.04 (BW), measured with DSS Off at 30 IRE
Signal to Noise Ratio (SNR)	±50 dB
PTZ	
Pan Travel	360° continuous
Tilt Travel	-10° to 190°
Manual Speed	0.13° to 90° / sec
Horizontal Viewing Angles	65.3° (Wide) to 2.2° (Tele)
Presets	256
Preset Accuracy	0.225°
Preset Speed	5° to 400° / sec
Maximum Pan-Tilt Speed	400° / sec
Sequence	8
Auto Pan	4
Pattern	8
Auto Flip	Digital / Mechanical / Off
Proportional Pan & Tilt	On / Off (pan and tilt speed proportional to zoom ratio)
Resume After Power Loss	Yes
Home Function	Preset / Sequence / Auto Pan / Pattern
Alarm	
Alarm	Input: 4 dry alarm contact Output: 2 relay contact, 30 VDC at 2A or 125 VAC at 0.5A max
Alarm Reaction	Preset / Sequence / Auto Pan / Pattern
Electrical	
Input Voltage	PoE++ 802.3at 60W (indoor/outdoor), PoE+ 802.3at 25W (indoor only), AC 24V ±10%
Power Consumption	Max 20W indoor (CP-4221-300), Max 60W outdoor (CP-3221-301) with heater operating
Power Connector	Terminal block

## Camera Ordering Information

Type	Series	Camera Resolution	Included Analytics	Lens Option	Environmental
CP	42	2	1	XX	X
PTZ Camera	42 = Quasar Series	2 = HD 1080p	1 = Intelligent Multi-zone VMD and Tamper Detection	30 = 30x Optical Zoom	0 = Indoor Tamper Resistant 1 = Outdoor IP66 Vandal with Heater/Fan

Video	
Compression	Dual Streaming H.264 / H.264 or H.264 / MJPEG
Maximum Performance	30fps @ HD 1080p + 30fps @ D1 or 15+15 @ HD 1080p
Resolution Range	Scalable from CIF to HD 1080p
Bandwidth	Configurable between 64 Kbps and 8 Mbps
Rate Control	CBR / VBR
SD Card Recording*	SDXC up to 64 GByte
Audio	
Bi-Directional Audio	Full duplex, line / mic in and line out, G.711, G.726
Bandwidth	Configurable between 16 kbps & 64 Kbps (depending on compression method)
Audio Connections	Terminal block
Network	
Network Protocols	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, SNT, IEEE 802.1X, QoS, ONVIF Profile S
Ethernet	10 / 100 Base-T auto sensing, half / full duplex (RJ45)
Configuration	Remote: via web access or supported video management software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network (1GB Flash / 2GB RAM)
Supported Web Browser	Internet Explorer 6.0+
Security	User account and password protection**
Physical	
Enclosure Rating	Tamper resistant surface mount or IK10 rated vandal IP66 outdoor housing
Dimensions	CP-4221-300: 171.7 x 228.71 mm (6.76 x 9 in.) CP-4221-301: 191.97 x 282.11 mm (7.55 x 11.1 in.)
Unit Weight	CP-4221-300: 1.62 Kg (3.57 lbs.) CP-4221-301: 2.32 Kg (5.11 lbs.)
Mechanical	
Bubble Rating	IK10 vandal resistant polycarbonate
Bubble F-Stop	F0.0 - clear bubble
Environmental	
Operating Temperature	CP-4221-300: 0° to 40° C (32° to 104° F) CP-4221-301: -45° to 50° C (-49° to 122° F)
Storage Temperature	-20° to 70° C (-4° to 158° F)
Humidity	95% (non-condensing)

## Warranty & Regulatory

Warranty	According to FLIR RMA Policy and Process Notice document
USA	UL, FCC Part 15 (subpart B, class A)
International	CE marked, EN55022-1998 class A, EN55024, RoHS

## Accessories

A complete list of mounts, brackets, pole mounts and recess kits for cameras can be found in the FLIR Price List and Camera Accessory Guide.

\*Excluding countries where disallowed

\*\*Quasar cameras are auto authenticated and discovered automatically by the Latitude VMS

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
PH: +1 877.773.3547

**CANADA**  
FLIR Systems - Canada  
250 Royal Crest Court  
Markham, Ontario,  
Canada L3R 3S1  
PH: +1 888.425.6739

FLIR Systems, Inc.  
6769 Hollister Ave,  
Goleta, CA 93117

www.flir.com  
NASDAQ: FLIR

FLIR Systems, Inc.  
65 Challenger Rd  
Ridgefield Pk., NJ 07660  
PH: +1 201.368.9700

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2016 FLIR Systems, Inc. All rights reserved. 05/2016

